MATERIAL SAFETY DATA SHEET

Fringe Cleaner

SECTION 1: Product Identification

Product name: Fringe Cleaner

Chemical family: cleaning solvent blend Common or trade name: cleaning agent

Formula: proprietary

Description: cloudy white liquid-lemon scent

SECTION 2: Hazardous Rating (NFPA 704 criteria)

Hazard Rating Scale

4=Severe

Health: 1 3=Serious
Fire: 1 2=Moderate
Reactivity: 0 1 =Slight
Special: 0 0=Minimal

Isoparaffinic Hydrocarbon CAS 64742-47-8

SECTION 3: Hazardous Ingredients

Citrus Terpenes CAS 5989-27-5

2-Propanol, 1-Methoxy CAS 107-98-2

152 PPM N/A Exxon Mobil Generally Recognized as Safe 100 PPM 150 PPM ACGIH 400 PPM 500 PPM ACGIH N/A N/A N/A

N/A

TLV(TWA) TLV(STEL) BASIS

2-Propanol CAS 67-63-0

Sodium Dithionite CAS 7775-14-6

Sodium Bisulfite CAS 7631-90-5

Sodium Carbonate CAS 497-19-8

400 PPM

N/A

N/A

N/A

Sodium Carbonate CAS 497-19-8

Generally recognized as Safe

SECTION 4: Fire and Explosion Data

Flash point: mixture will not burn Flammable limits: not applicable

Extinguishing media: use appropriate extinguishing media for material that is supplying fuel. Special fire fighting procedures: Firefighter should wear self-contained breathing apparatus.

SECTION 5: Health Hazard Data

Effects of overexposure:

A. Eye contact: burning feeling and irritation

B. Ingestion: gastric irritation

C. Inhalation: may produce dizziness and headache

D. Skin contact: skin irritant

Carcinogenicity: No ingredients listed as a carcinogen by IARD, NTP, OSHA, or ACGIH.

SECTION 6: Emergency First Aid Procedures

- A. Eye contact: flush with water for 15 minutes, if irritation persists, seek medical care
- B. Ingestion: do not induce vomiting, contains petroleum hydrocarbons, get medical attention immediately
- C. Inhalation: remove to fresh air, if problem continues seek medical care
- D. Skin contact: flush with warm water

MATERIAL SAFETY DATA SHEET

Fringe Cleaner

(page two)

SECTION 7: Handling Procedures

A. Protective equipment:

Eyes: do not spray in eyes, goggles may be used

Skin: chemical resistant gloves may be used if hypersensitive to product. Avoid pro

longed contact with skin. Remove and wash soaked clothing or shoes.

Inhalation: use in well ventilated areas only, if ventilation is poor or if hypersensitive to

product, use chemical (carbon) respirator

B. Storage: keep containers from freezing, store away from oxidizing materials, keep tightly sealed.

C. Ventilation requirements: Provide for ventilation (HVAC system, cross breeze, fans, etc.) during application and thereafter until areas are completely dry.

SECTION 8: Spill or Leakage Control Procedures

Flush spill area with plenty of water or absorb liquid with cloths, sawdust, floor absorbent, vermiculite, etc., and dispose of in accordance with applicable regulations. Keep this, and all other chemicals, out of surface waters, storm sewers, and other waterways entering or leading to ground and surface waters.

SECTION 9: Physical Data

The following data is approximate or typical values and should not be used for precise purposes or product specification.

Boiling range:

198°F to 202°F

Viscosity:

Water Thin

pH:

10.9

SECTION 10: Reactivity Data

Stability:

stable

Hazardous polymerization:

will not occur

Conditions to avoid:

strong oxidizing agents (bleach)

Incompatibility:

oxidizing agents (bleach)

Hazardous decomposition products:

sulfur dioxide

Inventories: All components of this product are listed on the EPA's TSCA inventory.

The information in this Material Safety Data Sheet is drawn from recognized sources believed to be reliable but is provided without warranty.

The user must determine safe conditions and assume liability for and loss, injury, damage, or expense resulting from use of this product.

Prepared by: Chem Max® Corp. (231) 798-7980 I

Date: 2/2006