

MATERIAL SAFETY DATA SHEET

MAXOUT

SECTION 1: Product Identification

Product name : MAXOUT
Chemical family : Cleaning Solvent Blend
Common or trade name: Carpet Cleaning Prespray
Formula: Proprietary
Description : Cloudy White Liquid-Lemon Scent

SECTION 2: Hazardous Rating (NFPA 704 criteria)

Hazard rating Scale:
4=Severe
3=Serious
2=Moderate
1=Slight
0=Minimal

Health	1
Fire	1
Reactivity	0
Special	0

SECTION 3: Hazardous Ingredients

	TLV(TWA)	TLV(STEL)	BASIS
Synthetic Aliphatic Hydrocarbon Cas 64742-48-9	175 PPM	N/A	Exxon Mobil
Citrus Terpenes (5989-27-5)	Generally Recognized as Safe		
Methoxypropanol (107-98-2)	100PPM	150PPM	ACGIH
Isopropanol (67-63-0)	400PPM	500PPM	ACGIH

SECTION 4: Fire and Explosion Data

Flash point: 115° F to 120° F
Flammable limits: None established
Extinguishing media: Use appropriate extinguishing media for material that is supplying fuel
Special fire fighting procedures: Firefighter should wear self-contained breathing apparatus

SECTION 5: Health Hazard Data

Effects of overexposure:
A. Eye contact: Burning feeling and irritation
B. Ingestion: Gastric irritation
C. Inhalation; May produce dizziness and headache
D. Skin contact: Skin irritant
Carcinogenicity: No ingredients listed as a carcinogen by I.A.R.D., N.T.P., O.S.H.A., or A.C.G.I.H.

SECTION 6: Emergency First Aid Procedures

A. Eye contact: Flush with water for 15 minutes. If irritation persists, seek medical care
B. Ingestion: Do not induce vomiting. Contains petroleum hydrocarbons. Get medical attention immediately
C. Inhalation; Remove to fresh air. If problem continues seek medical care.
D. Skin contact: flush with warm water

MATERIAL SAFETY DATA SHEET

MAXOUT

(page two)

SECTION 7: Handling Procedures

A. Protective equipment:

Eyes: Do not spray in eyes. Goggles may be used.

Skin: Chemical resistant gloves may be used if hypersensitive to product. Avoid prolonged contact with skin. Remove and wash soaked clothing or shoes.

Inhalation: Use in well ventilated areas only. If ventilation is poor or if hypersensitive to product, use chemical (carbon) respirator.

B. Storage: Keep containers from freezing, store away from oxidizing materials, keep tightly sealed

C. Ventilation requirements: Provide for ventilation (HVAC) system, cross breeze, fans, etc.)

During application and thereafter until areas are completely dry.

SECTION 8: Spill or Leakage Control Procedures

Flush spill area with plenty of water or absorb liquid with cloths, saw dust, floor absorbent, vermiculite, etc., and dispose of in accordance with applicable regulations. Keep this, and all other chemicals, out of surface waters, storm sewers, and other waterways entering or leading to ground and surface waters.

SECTION 9: Physical Data

The following data is approximate or typical values and should not be used for precise purposes or product specification.

Boiling range: 198° F to 202° F
Viscosity: Water Thin
pH: 10.7 in concentrate

SECTION 10: Reactivity Data

Stability: Stable
Hazardous polymerization: Will not occur
Conditions to avoid: Strong Oxidizing agents
Incompatibility: None Known
Hazardous decomposition products: None Known

The information in this material Data Sheet is drawn from recognized sources believed to be reliable but is provided without warranty.

The user must determine safe condition and assume liability for and loss, injury, damage, or expense resulting from use of this product.

Prepared by: Chem Max® Corp., (231) 798-7980

Date: 3/07