

TECHNICAL DATA SHEET

Fluorosolve® rayon

Description:

Fluorosolve® rayon is not an ordinary fiber protector, it is an extraordinary fiber protector specifically designed for rayon fibers. It incorporates the proper chemistry for rayon and other regenerated cellulosic fibers including: viscose, artificial silk, art silk, nitro silk, bamboo silk, lyocell, tencel, cuprammonium, vegan silk, bemberg, polynosic, modal, acetate, saponified acetate, triacetate and many more trade names, Fluorosolve® rayon provides extraordinary water repellency enabling it to prevent the yellowing or making it easier to remove the yellowing from rayon fibers. Fluorosolve® rayon protects fibers from dry soils, oily soils and water based stains. Plus it contains U.V. blockers to protect from sun light damage.

Directions:

Provide adequate ventilation. Ready to use. Do not mix with water. Shake well and pour onto a Fluorosolve sprayer. Do not mix with any other chemical. Lightly spray apply to new or just cleaned carpets, rugs, and upholstery. Use a 8002, 8003 or 8004 size tip. Spray evenly with overlapping passes. Do not exceed 40 P.S.I. Do not use electrical or compressor driven sprayer to apply. Fluorosolve® rayon will dry in 2 to 4 hours. Full protection requires another 24 hours of curing time. Do not saturate material. Each gallon of Fluorosolve® rayon will protect approximately 300 to 500 square feet of carpet. High density rugs may require more Fluorosolve® rayon. Upholstery fabric can be protected with coverage rate of 1000 to 1600 square feet of material (3 to 4 average sofas). Wipe overspray off adjacent floor, wall and furniture surfaces. Only use in a well ventilated area.

Caution:

Read safety data sheet (SDS) before using. Fluorosolve® rayon should not be applied to hard surfaces and other non-textile materials, including: metal, glass, plastic, leather, suede, and others. We recommend that you test before applying Fluorosolve® rayon. Test in a small inconspicuous area. Wait until dry and see if there are any adverse effects (I.E. color change, rings, adhesive movement). Do not apply if there are any adverse effects.

Note:

No PFAAS, PFOA or PFOS.

Special feature:

Fluorosolve® rayon will retard the yellowing that occurs with many rayon fibers. Remember that rayon is the lowest cost fiber and the lowest performing fiber. Rayon is easy to stain and discolor, it can even self-stain in a humid environment. Fluorosolve® rayon can turn rayon fibers into non-staining fibers. Rayon needs all the help that it can get.